



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

A502 GREASE

A502 Grease is a heavy-duty multi-purpose grease proven to be outstanding for chassis and bearing lubrication. It is fortified with extreme pressure agents to provide protection even when the best conventional lubricants fail quickly. The extreme pressure agents protect the bearing from scoring and destructive wear under the highest loading conditions.

- *MULTI-PURPOSE GREASE
- *SUPERIOR EXTREME PRESSURE PERFORMANCE
- *REDUCED WEAR
- *HIGHLY WATER RESISTANT
- *WIDE OPERATING TEMPERATURE RANGE (-30°F. TO 300° F.)
- *OUTSTANDING RUST & OXIDATION RESISTANCE

TYPICAL PROPERTIES

NLGI Grade	2
Rust & Oxidation	Nil
Timken OK Load, Lb.	45
Dropping Point, °F.	360
Base Oil Viscosity, SUS @ 100°F	900 – 1100
Base Oil Viscosity, SUS @ 210°F	78 – 90
Base Oil ISO Grade	approx. 220
Color	Amber
Texture	Smooth-Buttery

ALSO AVAILABLE: A501 Grease (NLGI Grade 1)
A500 Grease (NLGI Grade 0)
A5000 Grease (NLGI Grade 00)
A50000 Grease (NLGI Grade 000)

PACKAGING: 400 Lb. Drums, 120 Lb. Kegs, 45 Lb Pails, 14.00 ounce cartridges