



4646 Baker Avenue Cincinnati, Ohio 45212 USA Telephone 513-531-1777
Sales@interlubecorp.com www.interlubecorp.com

TECHNICAL DATA SHEET

ChainSaw Bar Oil 136W

Overview: Interlube ChainSaw Bar Oil 136W is a specially formulated chain saw lubricant designed to extend the life of the bar, chain and sprocket on chain saws. The EP, polymer and other additives in this lubricant give it excellent wetting characteristics allowing it to reach all areas that need lubrication and reduces the wear on all parts of the saw. Its tackiness helps it to adhere to the chain at high speeds encountered while in operation.

Operational Benefits: These products offer these competitive advantages to enhance your reliability:

• **Extreme pressure formulation** • **Adhesion polymer for maximum coverage** • **Excellent chain wetting** • **All-season use** • **Anti-wear for chain pins/ sprockets** • **Environmentally Friendly** • **Mildly caustic** • **Safe for use in food production** • **Mix with plant/city water** • **Leaves behind no residue**

Application: For use on all Chainsaw bar and chain lubrication systems

Typical Industries: This product is commonly used (but not exclusively) in the following industries:

• **Logging** • **Ice sculpturing**

Technical Properties

Specification	Method	Typical Results
Appearance	ASTM E-2680-16	Dark Brown
Specific Gravity	ASTM D-1298	0.87
Flash Point (°F)	ASTM -D93	>400
Pour Point (°F)	ASTM D-97	-25
Four Ball Wear (mm)	ASTM D-2266	0.26
Copper Corrosion	ASTM D-4048	1b
Rust Protection	ASTM D-1743	Pass

The values shown are typical of current production. All of them may vary within tolerable ranges

ChainSaw Bar Oil 136W is a all-season product. However, if a heavier viscosity is required or wanted, use our **ChainSaw Bar Oil 500S**. **Chain Saw Bar Oil 500S** has the same properties while blended in a heavier base.

28625

International Manufacturer & Distributor of the World's Finest Lubricants & Cleaning Compounds



The values shown are typical of current production. All of them may vary within tolerable ranges.

28625

International Manufacturer & Distributor of the World's Finest Lubricants & Cleaning Compounds