



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
 ☎ TELEPHONE 513-531-1777 • FAX 513-531-0193
 SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

ENDURA GEAR LUBES NON DRIP

Endura Gear Lubes are multi-viscosity, multi-purpose polymer gear lubricants designed to give total performance over wide temperature ranges for essentially all gear applications. They are formulated to give outstanding performance in the most severe industrial, automotive and heavy-duty trucking applications. The industrial applications cover all enclosed gearbox applications including worm gears. The automotive and heavy-duty trucking applications include high performance hypoid gears and limited slip differentials. Incorporation of polymers gives them true multi-viscosity performance to cover for wide temperature fluctuations due to daily and seasonal changes. They also contain special polymers to improve on the oil's ability to adhere to the gear and bearing surfaces under the most severe conditions and to reduce leakage. All of these factors add up to reduced maintenance, decreased downtime and improved performance.

TYPICAL PERFORMANCE

Exceeds AGMA Requirements

Worm Gear Performance Applications

MIL-PRF-2105E

API GL-5

API MT-1

Mack GO-J

SAE J2360

Limited Slip Differential Applications

Meets requirement of USDA H-2 material

TYPICAL PROPERTIES

Endura Gear Lube	SAE 80W-90 Non Drip	90-140 Non Drip
API Gravity	26.8	26.4
Viscosity @ 210°F, SUS	98	143
Viscosity @ 10°F, cp		35,000
Viscosity @ -15°F, cp	62,000	
Viscosity Index	120	115
Flash Point, °F	420+	425+
Pour Point, °F	-25	-20