



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

Endura Polymer Grease HD 252

Endura Polymer Grease HD 252 is a premium, very heavy duty, EP containing, multi-purpose grease designed for Industrial, Off Road, Mining, Construction, Farm and Transportation applications. It meets tough NLGI Certification Tests for multi-purpose greases and is extremely water resistant and adhesive. It is formulated with a premium performance package of high film strength agents, EP (Extreme Pressure) agents and AW (Antiwear) agents to give it superior load carrying and protective properties. The polymers incorporated in the formula increase the adhesiveness and shock load carrying abilities of the grease. Its own unique combination of additives and premium quality base stocks make it a truly heavy duty multi-purpose lubricant.

- * Superior High and Low Temperature Performance
- * Highly Adhesive - Stays Put - Cushions Shock Loads
- * High EP-AW Performance
- * Excellent Water Resistance
- * Outstanding Rust & Corrosion Performance
- * Meets USDA H2 Requirements where no possibility of food contact

Typical Properties

Appearance	Smooth, Red, Tacky
NLGI Grade	2
Penetration 60 Strokes, 77°F, 0.1mm	265 - 295
Dropping Point, °F	500 +
Timken OK Load, 10 minutes (ASTM D2509), lbs.	60
DI Rust Protection, 48h/52°C (ASTM D1743)	PASS
Viscosity – Base Oil, SUS @ 100° F	1100
Viscosity – Base Oil, SUS @ 210° F	88
Water Washout, 1 Hr/79° C (ASTM D1264), %	2.6