



INTERLUBE CORPORATIONTM
4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

FORMULA 1503 CONCRETE FLOOR CLEANER

A granular, dustless powder cleaner for removal of grease & heavy soil build-up from unpainted concrete floors, waste cans, storage areas, grease pits, loading docks, engine rooms, locker rooms, hangers, garages, driveways, etc. It converts the oil and grease into a soluble state, emulsifies them, and lifts them off the surface so they can be easily rinsed away.

WATER SOLUBLE: May be used with either hot or cold water. Involves absolutely no mixing with any flammable solvents, thus enabling safe removal of oil & grease, and eliminating fire hazards.

TIME SAVING: Formulated with special wetting agents in high concentration that speed the cleaning process so that no laborious scraping, scrubbing, or lengthy soaking is needed. It quickly enters cracks and surface irregularities to extract the soil. Will neither pit nor damage surfaces.

SAFETY FEATURES: Non-Flammable, Non-Hazardous, no noxious odors.

PROPERTIES

COLOR	Orange Powder Yellow Green Solution
EMULSIFICATION	Complete
pH 1% SOLUTION	12+
WETTING ABILITY	Rapid
BIODEGRADABLE	Yes

USE PROCEDURES: highly concentrated for economical use.

FOR AVERAGE FLOORS: Use 2 oz Formula 1503 per 1 gallon of water. Dissolve completely. Then mop & rinse.

FOR HEAVY SOIL: Wet surface with water. Sprinkle Formula 1503 lightly over wetted area. Brush in with stiff bristle brush. Allow to soak for just 3-5 minutes. Hose away.

FOR WASTE CANS: Use 1 cup Formula 1503 per pail of water. Scrub inside and outside with soft bristle brush. Steam rinse or hose down.

FOR MOPS, BROOMS, ETC: Mix solution of 2 oz Formula 1503 per 1 gallon of water.