



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

Formula 017

Interlube's Formula 017 is designed for light to heavy duty forming operations and light to moderate duty drawing applications. It has unique properties as a forming and stamping lubricant due to its exceptional wetting and cleaning ability as well as its lubricating capabilities. It finds use in a wide range of forming and stamping operations as well as some coining applications. Another major benefit of Formula 017 is that it does not leave unwanted residues, which require extensive and expensive cleaning operations. You can use it to do the forming operation and proceed to subsequent operations or final use applications without a cleaning step.

Formula 017 is an exceptional multi-purpose product, which is safe on all metals and most plastics. It can be dipped, rolled, sprayed, brushed, wiped or otherwise transferred prior to the operation. Application just prior to the operation is recommended. It is used just as it comes out of the drum. It normally does not require use of other additives or diluents and should be used as is. It does not cause staining or discoloration. Formula 017 complies with FDA Regulations 21 CFR 178.3530 and 21 CFR 178.3650 making it suitable for use in food grade material manufacturing.

Typical Properties

Color & Appearance	Clear - Water White
API Gravity	55.0
Specific Gravity	0.76
Pounds per Gallon	6.3
Flash Point, ASTM D 56	> 125° F