



Interlube

Corporation

4646BAKERAVENUE • CINCINNATI, OHIO 45212-2594USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORP.COM • WWW.INTERLUBECORP.COM

Formula 101X24C Heavy Duty Hammer and Chisel Paste

Formula 101X24C Heavy Duty Hammer and Chisel Paste is a specially formulated grease for hydraulic hammers and other impact tools that require protection from shock loads. It is a high temperature and extreme pressure grease, fortified with copper and graphite that forms a protective film that reduces wear of contact surfaces.

Benefits

- High dropping point
- High film strength that reduces metal to metal contact
 - Water and corrosion resistant
 - Reduces wear caused by shock loads
 - High load carrying properties
- High oil viscosity for improved load carrying

Typical Properties

Color	Black
Texture	Smooth
Thickener Type	Calcium Sulfonate Complex
NLGI Grade	2
Penetration @ 77 F, ASTM D 217, 0.1 mm Worked 60 Strokes	265 - 295
Base Oil Properties, Viscosity SUS @ 100 F	2400
Dropping Point, ASTM D-2265, F	> 500
4 Ball EP Test, ASTM D-2596, Weld Point, Kg	800
4 Ball EP Test, ASTM D-2596, Load wear index	65
Rust Test Rating, ASTM D-1743	Pass