
Formula 61 – Press Ink Cleaner

Overview: Interlube Formula 61 Press Ink Cleaner is a unique food grade multi-purpose cleaner and degreaser designed for removing oils and resin-based inks, oils, grease, dirt, particulates, and other oil soluble stains and debris from equipment used in the printing industry and related processes. This product is a very low viscosity fluid which has exceptional wetting and cleaning ability. It is very low odor and excellent solvency. If used properly, the Formula 61 Press Ink Cleaner doesn't leave unwanted residues or films which require further wiping and cleaning. It also is compatible with most common roller materials and won't cause softening or adhesion.

Formula 61 Press Ink Cleaner is a food grade material which meets US FDA requirements for incidental contact with food products and also meets the requirements for USDA H-1 requirements. It is non-hazardous and can be shipped under DOT less restrictive requirements.

Operational Benefits: These products offer these competitive advantages to enhance your reliability:

• **Very low foaming** • **Safe for use on all metals and most plastics** • **No mixing – Ready for use** • **Does not require heating** • **Does not require special equipment – Can be applied by light wiping** • **Does not freeze** • **Higher flash point than mineral spirits and many other solvents**

Application:

• **Press rolls** • **Printing equipment** • **Component cleaning prior to assembly**

Typical Industries: This product is commonly used (but not exclusively) in the following industries:

• **Printing** • **Food / Pet Food manufacturing** • **General manufacturing**

Note: *Use as purchased (no mixing required). It can be applied by dipping, hand wiping, spraying, wash cabinet*

Interlube Corporation

4646 Baker Avenue • Cincinnati, Ohio 45212-2954 USA • Telephone 513-531-1777

sales@interlubecorp.com • www.interlubecorp.com

International Manufacturer & Distributor of the World's Finest Lubricants & Cleaning Compounds

Formula 61 Press Ink Cleaner

Technical Properties

Property	Method	Typical Results
Appearance	Visual	Clear water-white liquid
API Gravity	ASTM D-4052	46 - 50
Specific Gravity @ 60°F	ASTM D-4052	0.78
Density (lbs/ gal)	---	6.5
Base Oil Type	---	Mineral
Viscosity cSt @ 40°C SUS @ 100°F	ASTM D-445	6.0 31.5
Flash Point, °C (°F)	ASTM D-93	73.9 (165)
Pour Point °C (°F)	ASTM D-97	-40 (-40)

The values shown are typical of current production. All of them may vary within tolerable ranges.

Interlube Corporation

4646 Baker Avenue • Cincinnati, Ohio 45212-2954 USA • Telephone 513-531-1777
sales@interlubecorp.com • www.interlubecorp.com



25926

International Manufacturer & Distributor of the World's Finest Lubricants & Cleaning Compounds