



# INTERLUBE CORPORATION<sup>TM</sup>

4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA  
TELEPHONE 513-531-1777 • FAX 513-531-0193  
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

## Formula 99X124A Barrier Coating

Formula 99X124A Barrier Coating is a wax emulsion used in a variety of applications to improve performance in many industries, and to provide desired surface properties. It provides water and block resistance in paint and coating formulations, and imparts water repellency on wood and other products. Formula 99X124A Barrier Coating is used in the following industries:

- Automotive Care Products
- Paints
- Exterior Wood Protection
- Industrial Wood and Plastic
- Inks
- Varnishes
- Ceramics
- Textiles and Leather

### Typical Properties

Appearance	Cream-colored, semi-viscous fluid
Solids	Paraffin / Polyethylene Wax blend
Emulsifier	Anionic
% Solids	Approximately 39%
pH	9 - 10
Brookfield Viscosity, cps Spindle Number: 3 RPM: 60	<1000

Please contact Interlube Corporation for your specific need. Formula 99X124A Barrier Coating can be used in many other applications to impart water resistance, and dust control, or improve slip and lubricity to your process.