



INTERLUBE CORPORATION™

4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

HYDRAULIC OIL - AL

Hydraulic Oils - AL are premium quality antiwear, antileak, antifoam, and rust and oxidation inhibited hydraulic oils which meet the requirements of all major hydraulic pump manufacturers. They were developed for use in modern high pressure, high speed hydraulic systems to insure maximum pump wear protection, and to prolong the systems life.

These oils have many applications, other than in hydraulic systems, including those calling for non-detergent type oils. They are especially suited for bearing lubrication, circulating systems, non EP type gear applications, sprockets, chains, slides, linkages, couplings, spindles, electric motors, and all once through applications.

BENEFITS

REDUCED WEAR - LONGER EQUIPMENT LIFE

REDUCED OIL CONSUMPTION - LOWERS COSTS

REDUCED MAINTENANCE - INCREASED PRODUCTION

REDUCED MAINTENANCE - BETTER HOUSEKEEPING

REDUCED INVENTORY - MULTIPURPOSE PRODUCT

TYPICAL PROPERTIES

GRADE	10	20	30
SAE GRADE	10W	20W-20	30
VISCOSITY @			
100°F., SUS	165	310	510
210°F., SUS	44	53	64
AGMA NUMBER	<1	2	3
VISCOSITY INDEX	101	98	97
POUR POINT	-25	-25	-25