



4646 BAKER AVENUE CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 FAX 513-531-0193
SALES@INTERLUBECORP.COM WWW.INTERLUBECORP.COM

Industrial Gear Lube EP

Industrial Gear Lubes EP are heavy duty, premium grade, industrial gear and bearing lubricants designed to withstand the toughest industrial requirements. They are made with highly refined, high viscosity index base stocks and formulated with the latest additive technology. They cover a very wide range of viscosities from **ISO 46 to ISO 1500** grades, and the full range of **AGMA grades**. Their performance exceeds the AGMA EP requirements and those of US Steel Service Requirement 224.

- Excellent demulsibility
- Available in all ISO VG Grades
- Available in all AGMA Grades
- Rust and oxidation inhibited
- Resist foaming
- Extreme pressure formulation
- Prevents wear

TYPICAL PROPERTIES

FZG Spur Gear Test, Damaging Load Stage	12+
Four Ball Wear (ASTM D4172), mm	0.28
Four Ball EP (ASTM D2783), kgf	250
Timken OK Load (ASTM D2782), pounds	75
Viscosity Index	95+
ABC Corrosion, Bethlehem Steel	Pass
Steel Corrosion, Synthetic Sea Water (ASTM D665)	Pass
Pour Point, °F	-15 maximum

[International Manufacturer & Distributor of the World's Finest Lubricants & Cleaning Compounds](#)