



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

Open Gear Grease MHTG 15

Interlube Corporation's Open Gear Grease MHTG 15 is specially formulated to provide outstanding performance on all types of open gears and other industrial applications. It is fortified with extreme pressure additives, graphite and other solid additives to provide excellent protection to all lubricated surfaces. Open Gear Grease MHTG 15 coats the open gear with a tenacious, tacky, tough, water resistant film. The solid lubricants and other additives, provide outstanding protection against high loads and high temperatures that may be encountered in many applications.

- Tenacious lubricating film**
- Non-melt grease for high temperature applications**
- Excellent water resistance**
- High level of solids for heavy loads**
- Anti-Seize properties**
- Extreme pressure additives**
- High oil viscosity**
- NLGI 1.5 for easier handling**

Typical Properties

| | |
|-----------------------------------|------------------|
| NLGI Grade | 1.5 |
| Worked Penetration, mm/10 | 285 – 315 |
| Dropping Point, °F | None |
| Oil viscosity, SUS @ 100°F | 2400 |
| Oil viscosity, SUS @210°F | 150 |