



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

Petro White

| | |
|------------------------------------|---------------------|
| Appearance | Smooth, clear white |
| NLGI Grade | 4 |
| Penetration 60 Strokes, 77°F | 187 |
| Dropping Point, °F | 130 |
| Viscosity @ 210°F, SUS | 70 |
| Congealing Point (ASTM D938), °F | 123 |
| Volatile Organic Compounds (VOC's) | 0% |

Petro White provides very effective, clear white coating that provides a protective barrier in paint booth applications. It is ideal for any area of the paint booth, including lighting due to its clarity. Petro White should be used as received without any dilution. Application can be performed in many ways based upon the equipment available. It can be simply applied as is with brushes or rollers, however, this could be difficult in cooler environments as it does set up fairly hard when cool. The easiest application method is to heat up the Petro White to 130°F to 140°F as it will become a liquid. Then it can be easily applied by brush, roller or spray system. As it cools on the applied areas, it will solidify and set up. After painting operations are complete, Petro White is easily removed with scraping, as the film remains soft.

Petro White contains no harsh or environmentally harmful solvents (no VOC's).

06515