



**INTERLUBE CORPORATION**<sup>TM</sup>  
4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA  
☎ TELEPHONE 513-531-1777 • FAX 513-531-0193  
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

## VACUUM PUMP OIL 55

Vacuum Pump Oil 55 is a special low volatility oil formulated to give superior oxidation resistance, excellent demulsibility, and improved anti-wear properties in addition to the good anti-wear and anti-foam properties of conventional vacuum pump oils. Its oxidation resistance and anti-wear properties are three to five times better than those of conventional rust and oxidation inhibited vacuum pump oils. The special low volatility oils assure efficient pump operation.

- \* Superior Oxidation Resistance
- \* Excellent Demulsibility
- \* Anti-Wear Properties
- \* Good Rust & Anti-Foam Properties
- \* Very Low Temperature Flow Properties
- \* High Flash Point

### TYPICAL PROPERTIES

Viscosity, SUS @ 1001 F	340
SUS @ 2101 F	56
Viscosity Index	100
Flash Point, 1 F	430
Vapor Pressure, mm Hg @ 681 F	<0.0001
Specific Gravity	0.87

Comments or Notes:

Interlube Sales Representative: