



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA  
TELEPHONE 513-531-1777 • FAX 513-531-0193  
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

## WG-SERIES - FIRE RESISTANT HYDRAULIC FLUID

Interlube's WG-Series Fluids are specially formulated water-glycol fire resistant hydraulic fluids which meet both high pressure pump requirements and the most severe fire resistant qualifications.

### TYPICAL PROPERTIES

### WG-200

Viscosity at 100° F, SUS	200
Specific Gravity, 60/60 °F	1.081
Pour Point, ° F.	-40
Flash Point, ° F	None
Fire Point, ° F	None
Appearance	Viscous      Red
Liquid	
pH	9.6

**FIRE PROTECTION** - All WG-Series Fluids pass Factory Mutual "less hazardous hydraulic fluids" tests (but are not registered nor certified) and WG-200 is rated as a "permissible fire resistant hydraulic fluid" by the U.S. Bureau of Mines.

**WEAR PROTECTION** - The WG-Series fluids are designed to pass a 2000 psi pump wear test using a Vickers VK 105C pump.

**CORROSION PROTECTION** - The WG-Series fluids contain both liquid and vapor phase corrosion inhibitors to provide complete corrosion protection for your hydraulic system.

**COMPATIBILITY** – Interlube's WG-Series fluids are compatible with all high quality water-glycol fire resistant hydraulic fluids, in any proportion. They are NOT compatible with other types of hydraulic fluids, such as oils, water-oil emulsions, synthetic phosphate esters, or ester based fluids, and should not be mixed with these products.