



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA  
 ☎ TELEPHONE 513-531-1777 • FAX 513-531-0193  
 SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

## White Cote Super T-2

White Cote Super T-2 is a superior multi-purpose food grade grease, specially formulated for moderate to high temperature applications where water or steam may be present. It has outstanding water resistance, superior oxidation resistance and extremely high load carrying performance. This special food grade grease formulation, meets US FDA regulations for a H-1 type lubricant. Its unique formulation gives it unsurpassed EP and Anti-wear properties and exceptionally long service life.

It has superior shear-stability and lubricating properties over all conventional greases. It also has an operating temperature range from - 30° F to +400° F and has exceptionally high EP performance and superior rust and oxidation resistance. This “Super” grease is compatible with nearly all other types of greases.

It is designed for use by Bakeries, Bottlers, Breweries, Canning Companies, Dairy and Dairy Products Manufacturers, Meat, Fish, and Poultry Processors, Can Manufacturers, Candy Manufacturers, Cookie and Cracker Manufacturers, Snack Food Manufacturers, and a very large number of other industrial food and drug manufacturing applications.

- \* Meets USDA H-1 Requirements
- \* Wide Operating Temperature Range
- \* Superior Shear Stability
- \* Exceptionally High EP Performance
- \* Outstanding Water Resistance
- \* Excellent Tack - Superior Adhesion
- \* Excellent Lubricity - Low Friction @ High Loads

### Typical Properties

NLGI Grade	2
Color	Tan
Appearance	Smooth
Texture	Tacky
Dropping Point, ° F	570
Water Washout, % @ 175° F, % loss	2.75
Timken OK Load, (ASTM D-2590)	65
Four Ball Weld, kg (ASTM D-2596)	620
Oxidation Stability, PSI Loss, 100 Hrs. @ 99°C (ASTM D-942)	1
Oil Separation, ASTM D 1742, %	0.2