

NON-CHLORINATED

Sprays as a deep penetrating liquid that flows into areas which are difficult to lubricate. Then, as the solvent carrier evaporates, the liquid forms into a grease that is resistant to high temperature and pressure. After setting up, the grease will not wash away with water or steam and will resist throw-off and heavy shock load. Withstands acid, salt spray and oxidation.

USE ON:

Wire rope, linkages, draglines, fittings, winches, cranes, cams, valves, cables, hoists, pulleys and rollers.

DIRECTIONS:

First, spray up close to flush off old grease and dirt build-up. Then spray a thin film on surface to be lubricated. Liquid will creep and penetrate then gel in approximately 15-20 minutes.

INTERLUBE CORPORATION
4646 Baker Avenue
Cincinnati, Ohio 45212 USA
Phone: (513) 531-1777
Fax: (513) 531-0193
www.interlubecorporation.com



RED SPRAY GREASE II

- **Lithium-Based**
- **High Temperature and Pressure Resistance**
- **Prevents Water Washout**
- **Withstands Harsh Chemical Environments**



NET WT. 11 OZ. (311 Grams)

DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
VAPOR HARMFUL. CONTENTS UNDER
PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.



DANGER:

Acetone (67-64-1), Naphtha (Petroleum), Hydro-treated Heavy (64742-48-9), Naphtha (Petroleum), Light Aliphatic (64742-89-8), and Carbon Dioxide (124-38-9). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

HMIS RATING:	
HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	B

MADE IN
CANADA

KEEP OUT OF REACH
OF CHILDREN

For further information
consult Material Safety Data Sheet.