



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA
TELEPHONE 513-531-1777 • FAX 513-531-0193
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

ROCK DRILL LUBRICANT

Interlube's Rock Drill Lubricants are especially formulated oils designed to meet the heavy duty performance requirements of all types of rock drills. They have exceptionally high film strength, offer superior rust protection, readily handle extreme pressure loads (Passes 300,000 PSI test), and meet the requirements of Gardner-Denver Rock Drill specifications. They contain many synergistic additives to achieve total performance.

- Highly Polar Compound – to reduce wear and give superior rust protection
- Extreme Pressure Agents – to withstand high loads and shock conditions
- Adhesives and Cohesive Agents – to assure a continuous lubricating film
- Emulsion Stabilizers – to assure proper operation under moist conditions
- Proper Lubricant Base Stocks – to assure low carbon and varnish build-up
- Normal Rust, Oxidation, and Antifoam Inhibitors

Three grades allow for a wide range of operational conditions:

VISCOSITY @ 100° F. (SUS)

LIGHT	230
MEDIUM	500
HEAVY	980
EXTRA HEAVY	1500